newline













Compatibility





Collaboration Hub

Security

THE UNMATCHED ALL-IN-ONE UNIFIED COLLABORATION SOLUTION

The X Series features an all-in-one solution for collaboration that is immersive, unified and effective. X Series is designed to make your meetings more efficient. The two built-in 1080p wide-angle cameras let you be seen from anywhere in the room. The microphone array reduces noise and cancels echo. Your voice can be heard clearly. Advanced InGlass touch enables responsive touch for a smooth and intuitive writing experience as natural as writing on paper. Optical bonding gives you an ultra-wide 178° viewing angle. No matter where you sit in the room, the image is robust and clear.

X Series allows you to meet, conference and collaborate without limitations. Share voice, video, data and annotations. Work on documents simultaneously with people on a conference call as if you were in the same room. With the instant digital discussion board and on-screen annotation tool, you'll never let another idea slip away.

Newline X series features the following optional interactive ecosystem tools:

CAST BROADCAST DISPLAY MANAGEMENT

WORKSPACE

LAUNCH**CONTROL**

Series



Model	X6	X8	Х9
		Display	
Backlight		LED	
Display Area	1431 × 806 mm	1662 × 942 mm	1897 × 1068 mm
Active Screen Size	65"	75"	86"
Display Ratio		16:9	
Resolution		3840 × 2160 Pixels	
Display Color Depth	8-bit	8-bit	10-bit
Brightness		370 nit	
Contrast Ratio	4000:1	4000:1	1200:1
Response Time	1000.1	8 ms	1200.1
·		178°	
Viewing Angle Life Time			
Life Time		≥ 30,000 hours Speaker	
Speaker Position		Front	
	8Ω		
Rated Impedance	80 - 18K Hz		
Frequency Response			
Output SPL		88 ± 3 dB	
Max. Power Output		15 W × 2	
		Microphone	
Sensitivity		-38 ± 3 dB	
Frequency Response	62 - 12.5K Hz		
Polar Patterns	Omnidirectional		
THD +N (1K Hz @ +4dBu)	0.25% at 104 dB SPL		
Quantity		4	
		Camera	
Position	Top × 1 , Bottom × 1 (Only one can be used at a time)		
Sensor	2M Pixels		
Lens		72°	
Video Resolution		1920 × 1080 @30fps (Max)	
	Maximum ≤ 250 W	Power Maximum ≤ 400 W	Maximum ≤ 450 W
Power Consumption	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W	Standby Mode ≤ 0.5 W
Working Voltage		AC 100-240 V, 50/60 Hz	
		Touch	
Touch Surface	Or	otical Bonding Anti-Glare & Anti-Fingerprint G	lass
Transparency	80% - 90%		
Haze		≤ 5%	
		7H	
Surface Hardness			
Touch Technology		InGlass	
HID Support		HID	
Touch Points		20 Points in Windows/ 10 Points in Android	
Writing Tools		Passive Pen/ Finger/ Palm	
Touch Resolution	22855 × 12856	26394 × 14847	30320 × 17055
Scan Speed		150 Hz	
Positioning Accuracy		±1.0 mm	
Communication Interface		USB-A	
	Environmental/ Physical Specifications		
		-15℃ - 55℃/ 20 - 90%RH	
torage Temperature/ Humidity	• •		
		0°C = 40°C/ 20 = 80°∕ PH	
Vorking Temperature/ Humidity		0°C - 40°C/ 20 - 80%RH	
Vorking Temperature/ Humidity Mounting (Optional)	1500 - 1045 - 20	Wall Mount/ Floor Stand	0000 1015 100
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions	1569 × 1045 × 89 mm	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm	2039 × 1315 × 103 mm
Vorking Temperature/ Humidity Mounting (Optional)	1725 × 275 × 1170 mm	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm	2155 × 310 × 1400 mm
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions	1725 × 275 × 1170 mm US 45 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg	2155 × 310 × 1400 mm US 71 kg
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight	1725 × 275 × 1170 mm US 45 kg EU 45 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg	2155 × 310 × 1400 mm US 71 kg EU 71 kg
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight	1725 × 275 × 1170 mm US 45 kg EU 45 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg	2155 × 310 × 1400 mm US 71 kg EU 71 kg
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2,	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg
Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs AV Inputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 11.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, 41 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Tou	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI HDMI C	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 11.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, 41 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Tou	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs AV Inputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI HDMI C	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 1.1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, 4l 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Touch) victory (Support 4K@60Hz) × 1, Line Out × 1, SPI ibedded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dynamic) victory (Support 4K@60Hz) victory	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs AV Inputs AV Outputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI HDMI C	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 11.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MI 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Tou out (Support 4K(@60Hz) × 1, Line Out × 1, SPI bledded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dy DC 5V-2A Out × 1	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs AV Inputs AV Outputs Other	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI HDMI C	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 11.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, All 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Touch) × 1, USB(Touch) × 1, Line Out × 1, SPI abedded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dynamic) × 2, Ut (Support 4K@60Hz) × 1, Line Out × 1, SPI abedded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dynamic) × 2, Ut (Support 4K@60Hz) × 1, Line Out × 1, SPI abedded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dynamic) × 2, Uther Features	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4
Vorking Temperature/ Humidity Mounting (Optional) Outline Dimensions Packing Dimensions Net Weight Gross Weight Front Interface Inputs AV Inputs AV Outputs	1725 × 275 × 1170 mm US 45 kg EU 45 kg US 57.5 ± 2 kg EU 57.5 ± 2 kg HDMI HDMI C	Wall Mount/ Floor Stand 1792 × 1169 × 103 mm 1918 × 275 × 1295 mm US 58 kg EU 58 kg US 72 ± 2 kg EU 72 ± 2 kg Connectivity 11.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MI 2.0 × 2, HDMI 1.4 × 1, DP 1.2 × 1, USB(Tou out (Support 4K(@60Hz) × 1, Line Out × 1, SPI bledded × 1, RS232 × 1, RJ45 × 2, USB 3.0(Dy DC 5V-2A Out × 1	2155 × 310 × 1400 mm US 71 kg EU 71 kg US 93 ± 2 kg EU 93 ± 2 kg MIC × 1 ch) × 4

newline

NEWLINE INTERACTIVE INC.

101 East Park Blvd. Suite 807 Plano, TX 75074, USA TEL: +1 888 233 0868

ASIA PACIFIC OFFICE

17F, No. 653, Bannan Rd, Zhonghe Dist, New Taipei City 235, Taiwan TEL: +886 2 8228 2089

EUROPE OFFICE

Ronda de Poniente, N'2, 1st floor, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178

INDIA OFFICE

Room No. 203, No. 37, TTK Road, Alwarpet, Chennai, Tamil Nadu, India, 600018 TEL: 1 800 419 0309

newline-interactive.com