

Display diagonal	26.5 Inches (672.85mm)
Active Display Area	475.78 x 475.78 mm
Resolution	1.920 x 1.920 (QHD) @ 60 Hz / 1:1
Panel Type	IPS Hard-Coating (3H), Anti-Glare Treatment
Brightness	450 cd/m2
Contrast	1.000:1
Viewing Angle	178° H/V
Colors	8 Bit + FRC, 16.7M colors
Color Gamut	NTSC 92%
Anti-Glare (Haze)	25%
Orientation	Landscape / Portrait
Connections	1x USB, 1x RJ out, 1x RJ45c, 1x RS232c, 1x Micro SD Card, 1x USB Type C (Power Supply)
Operation Time	24 / 7
Operating Conditions	Temperature 0°C to 50°C / Humidity 10-80%
Storage Conditions	Temperature -20°C to 50°C / Humidity 10-90%
Delivered Contents	Power Adapter, Mounting Plate
Integrated Computer	BrightSign 4K Player integrated (1920x1920px) VIDEO H.265/H.264 .MOV, .MP4, .MKV, .TS IMAGE BMP, JPEG, PNG WI-FI/Bluetooth Module (Optional)
Dimensions	493.9 x 493.9 x 35 mm (Even Thickness) / Bezel 7.4 mm (Even Bezel)
VESA	300 x 300 mm
Weight	2.9 Kg (Net)
Power Consumption	Operation 58W / Standby 0.5W (24V/6A, Source 100-240V 60W)
Certifications	CE
Warranty	2 Years Parts & Labor